

BEIGE



ATENAS

Wood Look
9x48


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

TAUPE



PERFORMANCE DATA

THICKNESS: 10.00 mm

CHARACTERISTIC	NORM	RESULT
Water Absorption	ISO 10545-3	≤ 0.5 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	> 38N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	0.49
Frost Resistance	ISO 10545-12	Frost Resistant
Chemical Resistance - Household	ISO 10545-13	Conforms
Chemical Resistance - Acids/Bases	ISO 10545-13	Conforms
Linear Thermal Expansion	ISO 10545-8	Conforms
Thermal Shock Resistance	ISO 10545-9	Conforms
Resistance to Stains	ISO 10545-14	Class 5

NOTES:

Per ANSI standard A108.02, 4.3.8.2, offset of the joints must be no more than 1/3 the length of the tile.

The Dynamic Coefficient of Friction (DCOF) is 0.49 wet. Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only.

Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An Appointment



www.tileamerica.com



GRIS