

FRESH



BLOOM



STREET



FRAME



BOARD



GLOW



BRETON

Italian Porcelain

12x24 Matte & Polished, 24x24 Matte & Polished, 2x2

Mosaics, 4x4.5 Hexagon Mosaic Honed


TILE

AMERICA

SHADE VARIATION

V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern within similar colors.



WEAR CODE

All Breton matte finish is rated (5) for all residential and commercial applications.

Bloom/Fresh/Street Polished are rated (4) for all residential and light commercial applications.

Glow Polished is rated (3) for all residential applications.

Frame/Board Polished is rated (2) for light residential applications.

PERFORMANCE DATA

THICKNESS: 9.00 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5 % (Matte)
Abrasion Resistance	ISO 10545-7	5 (Matte)
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction	AcuTest	≥ 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. Class B
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Min. Class 3

Notes:

Dynamic Coefficient of Friction (DCOF) for the matte finish is > 0.42 Wet.

Minimum Recommended Grout Joint for Rectified tiles is no less than 1/8".

Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com