

ALABASTER



SILVER



WINTERGREEN



GREIGE



CARLISLE

Italian Porcelain

12x24 Natural & Lappato, 24x24 Natural & Lappato,
3x3.5 Hexagon Mosaic, 2x3 Mosaic, 3x24 Bullnose


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

THICKNESS: 9.00 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	> 40 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	≥0.42 (Matte)
Thickness Dimension	ISO 10545-2	Compliant
Frost Resistance	ISO 10545-12	Frost Proof
Resistance to Stains	ISO 10545-14	Min Class 3
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. UB
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Min. UB

Notes:

Per ANSI standard A108.02.4.3.82, joints on tiles longer than 18" should not be staggered more than 1/3 the length of the tile.

Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only.

Variation in color and shading is to be expected.

Final selection should be made from actual tile samples.

Book An Appointment



www.tileamerica.com