

# CHATHAM TILE

Ceramic Tile


Matte & Glossy: 2.5x10, 3x6, 4x16, 4x8 Helongated

Hex.5x12 Wall

AMERICA

## SHADE VARIATION

V1 - Uniform Appearance  
Differences among pieces from the same production run are minimal.



## WEAR CODE

Class 1 Rated for wall application only

8.5mm Thickness: Matte and Glossy 3x6 and 2.6x10.25

9.0mm Thickness: Matte and Glossy 4x16 and .5x12

## PERFORMANCE DATA

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	> 10%
Abrasion Resistance	ISO 10545-7	1
Breaking Strength	ISO 10545-4	> 600 N
Dimensions Range	ISO 10545-2	Conforms
Chemical Resistance Household Chemicals	ISO 10545-13	GHA/GLA
Chemical Resistance Low Concentration of Acids	ISO 10545-13	GHA/GLA
Resistance to Stains	ISO 10545-14	Min Class 3
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

## Notes:

Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An  
Appointment



www.tileamerica.com

GLOSSY



MATTE

