

BIANCO



DECOR


Italian Porcelain
6x6

TILE

AMERICA

SHADE VARIATION

V4 - Random Color differences from tile to tile, so that one tile may have totally different colors from that of other tiles. Thus the final installation will be unique.



GRIGIO



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

AZZURRO



PERFORMANCE DATA

THICKNESS: 8.50 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	< 0.5%
Abrasion Resistance	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 35 N/mm2
Dynamic Coefficient of Friction	AcuTest	> 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Resistant
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

DECOR 03



DECOR 10



DECOR 07



Notes:

Dynamic Coefficient of Friction (DCOF) is > 0.42 Wet.
Minimum Recommended Grout Joint for Pressed tiles is no less than 3/16". Always inspect materials prior to installations.
Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com