

SPARK



ENCHANT

Wood Look

8x40, 8x40 Chevron, 2.5x20 Bullnose


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example “that little bit of color” on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

OASIS



PERFORMANCE DATA

THICKNESS: 9 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5%
Breaking Strength	ASTM C648	≥ 400 lbs
Chemical Resistance	ASTM C650	Conforms
Dynamic Coefficient of Friction Wet	AcuTest	0.42
Dimensions	ASTM C499	Conforms
Facial Range of Thickness	ASTM C499	Conforms
Warpage (Diagonal)	ASTM C485	Conforms
Wedging	ASTM C502	Conforms
Frost Resistance	ASTM C1026	Frost Resistant
Scratch Hardness	MOHS	6

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15” should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com

MYSTIC

