

ZINC



FOUNDRY26 TILE

Metal Look


2x2 Mosaics, 12x24

AMERICA

SHADE VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

V2 - Slight Variation



ALLOY



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use. (i.e., Shopping Malls, Hospitals)

PERFORMANCE DATA

THICKNESS: 9 mm

Characteristics:	Norms:	Results
Water Absorption	C373	≤ 0.5%
PEI Abrasion Resistance (Glazed)	C1027	NA
Breaking Strength	C648	≥400 lbs
Dynamic Coefficient of Friction Wet	AcuTest	0.55
Dimensions Range	C499	.5% (+/- 2 mm)
Facial Range of Thickness	C499	≤ 0.5% (+/- 2 mm)
Wedging	C502	≤ 0.5% (+/- 2 mm)
Frost Resistance	C1026	Frost Proof
Chemical Resistance	C650	Unaffected
Scratch Hardness	MOHS	7

OXIDE



RAIL



Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com