

BIANCO



GLACIER LAKE TILE

Italian Porcelain

AMERICA


2x2 Mosaics (Honed) , 1x3 Herringbone, .6x12 Pencil, 3x6, 4x8, 4x12, 12x12, 12x24

SHADE VARIATION

LIME



V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.



WEAR CODE

Azzurro Glossy/Bianco Glossy & Matte/Lime Glossy/Grigio Matte/Taupe Glossy & Matte: Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

Grigio Glossy/Nero Matte: Class 3 Residential Applications. Suitable for all residential applications.

Blu Glossy/Nero Glossy: Class 2 Light Residential Use. Must not be used in residential areas that are subject to constant or heavy traffic.

TAUPE



PERFORMANCE DATA

THICKNESS: 10 mm

AZZURRO



CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	0.51
Dimensions	ISO 10545-2	Conforms
Chemical Resistance	ISO 10545-13	Conforms
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Conforms
Frost Resistance	ISO 10545-12	Frost Resistant
Crazing Resistance to Glazed Tiles	ISO 10545-11	Resistant

GRIGIO



BLU



NERO



Notes:

Per ANSI standard A108.02,4.3.8.2, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile.

Dynamic Coefficient of Friction for plain field tile is greater than 0.42 wet.

Minimum recommended grout joint for this series is 3/16"

Book An Appointment



www.tileamerica.com