

HERITAGE TILE

AMERICA


Portuguese Tile
8x8

SHADE VARIATION

NOSTALGIA



V1 - Uniform Appearance
Differences among pieces from the same production run are minimal.



WEAR CODE


Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA


THICKNESS: 8 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.05 %
Abrasion Resistance (Glazed)	ASTM C1027	4/5
Breaking Strength	ASTM C648	≥ 140 kN
Dynamic Coefficient of Friction Wet	AcuTest	0.49
Dimensions	ASTM C499	Conforms
Facial Range of Thickness	ASTM C499	Conforms
Warpage (Diagonal)	ASTM c485	Conforms
Wedging	ASTM C502	Conforms
Frost Resistance	ASTM C1026	Frost Resistant
Bond Strength	ASTM C482	≥ 50 psi

TIMELESS



TRADITION



Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com