

MARQUINA
WHITE



STATUARIO
SUPERIORE



AREBESCATO



CENERINO



MARQUINA
BLACK



MARMI

Marble Look


2x2 Mosaic, 4x4.5 Hexagon Mosaic,
1x3 Herringbone Mosaic, 4x24, 12x24 Matte &
Polished, 24x24 Matte & Polished,
24x48 Matte & Polished,

Clearly distinguishable differences in texture and/or pattern within

TILE AMERICA

SHADE VARIATION

V2 - Slight Variation
similar colors.



WEAR CODE

Black Polished: 2 - Walls and Light Residential Floor Applications | Black Matte
and Cenerino Polished: 3 - Walls and Residential Floor Applications | All other
colors/finishes: 4 - Walls and Residential and Light Commercial Floor
Applications

PERFORMANCE DATA

THICKNESS: 9 mm

| Characteristics: | Norms: | Results |
|---|--------------|------------------------|
| Water Absorption | ISO 10545-3 | ≤ 0.5% |
| Abrasion Resistance | ISO 10545-7 | 2 / 3 / 4 |
| Breaking Strength | ISO 10545-4 | ≥ 35 N/mm ² |
| Dynamic Coefficient of Friction | AcuTest | ≥ 0.42 (Matte) |
| Dimensions Range | ISO 10545-2 | Conforms |
| Frost Resistance | ISO 10545-12 | Frost Proof |
| Chemical Resistance - Household Chemicals | ISO 10545-13 | Min Class 3 |
| Chemical Resistance - Low Concentration of Acids | ISO 10545-13 | Min Class 3 |
| Resistance to Stains | ISO 10545-14 | Min Class 3 |
| Crazing Resistance of Glazed Tiles | ISO 10545-11 | Resistant |

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An
Appointment



www.tileamerica.com