


PURE WHITE



SAND




GREY



TIFFANY




MINT



GREEN



DENIM



TERRACOTA



MARTINI

European Tile

2x6 Mate, Glossy and Stripes, y
.5x12 Glossy and Matte Quarter


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Martini Stripes is rated 1 for walls only, Martini light colors is rated 4 for for all residential and commercial applications and Martini dark colors is rated 3 for residential applications.

PERFORMANCE DATA

THICKNESS: 9 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5%
Abrasion Resistance	ISO 10545-7	3 / 4
Breaking Strength	ISO 10545-4	≥ 35 N/mm2
Dynamic Coefficient of Friction	AcuTest	> 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance Household Chemicals	ISO 10545-13	GA/GLA
Chemical Resistance Low Concentration of Acids	ISO 10545-13	GA/GLA
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Conforms
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

Notes:

Minimum Recommended Grout Joint for Non-Rectified tiles is no less than 3/16". Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com