

IVORY




OAHU

Wood Look

9.5x11 Hexagon, 2.5x24 Bullnose, 12x12
Intreccio Mosaic, 10x12 Hexagon Mosaic,
12x24

Clearly distinguishable differences in texture and/or pattern within

V2 - Slight Variation
similar colors.



TILE

AMERICA

SHADE VARIATION

WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

BEIGE




PERFORMANCE DATA

THICKNESS: 9.5 mm

| Characteristics: | Norms: | Results |
|--|--------------|-------------|
| Water Absorption | ISO 10545-3 | ≤ 0.1 % |
| Abrasion Resistance | ISO 10545-7 | 4 |
| Dynamic Coefficient of Friction | AcuTest | ≥ 0.42 |
| Dynamic Coefficient of Friction Wet | DCOF | > 0.42 |
| Dimensions Range | ISO 10545-2 | Conforms |
| Frost Resistance | ISO 10545-12 | Frost Proof |
| Chemical Resistance Household Chemicals | ISO 10545-13 | A-LA-HA |
| Thermal Shock Resistance | ISO 10545-9 | Resists |
| Resistance to Stains | ISO 10545-14 | Class 5 |
| Crazing Resistance of Glazed Tiles | ISO 10545-11 | Resists |

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.



Book An Appointment

www.tileamerica.com

SKY BLUE



HONEY

