

ARTIC



ORIGIN

Stone Look
3x24 Bullnose, 12x24


TILE

AMERICA

SHADE VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

V2 - Slight Variation



DESERT



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

THICKNESS: 9 mm

| Characteristics: | Norms: | Results |
|-------------------------------------|---------|-----------------|
| Water Absorption | C373 | ≤ 0.5 % |
| Chemical Resistance | C650 | Unaffected |
| Breaking Strength | C648 | ≥ 400 lbs |
| Dynamic Coefficient of Friction Wet | AcuTest | ≥ 0.42 |
| Dimensions | C499 | Conforms |
| Facial Range of Thickness | C499 | Conforms |
| Warpage (Diagonal) | C485 | Conforms |
| Wedging | C502 | Conforms |
| Frost Resistance | C1026 | Frost Resistant |
| Scratch Hardness | MOHS | 6 |

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 18" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com

CANYON



BOULDER

