

PAINT


Spanish Tile 3x12, 3x12 Deco Mix, 9x9, 8x9 Hexagon, 8x9 Hexagon Deco Mix,



SHADE VARIATION



V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.



KAKI



WEAR CODE

3x12: Class 1 - Wall Applications Only; Bianco / Grigio: Class 4 - Walls + Residential / Light Commercial Floor

Applications;

All others: Class 3 - Walls + Residential Floor Applications

BORDEAUX



PERFORMANCE DATA

THICKNESS: 10 to 11 mm

ъ. т	_	
I	F.	
	_	
	1	
	1	
	1	
	1	
	- 0	
	1	

ΑQ	UA	MA	RIN	Ε
	i.	7.1	,	
	•			40
	6			
				Same of the last
-				-5

	and the second s
ACTION.	
The state of the s	
7.	
Dir.	d
麗	Q.
20 1	3
	.1
E 400	
-	
	The second secon
	- 1
	The second secon

BLUE

Characteristics:	Norms:	Results
Abrasion Resistance	ISO 10545-7	1/3/4
Dimensions Range	ISO 10545-2	Conforms
Chemical Resistance - Household Chemicals	ISO 10545-13	А
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Conforms
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resists

NERO



Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

