

WHITE



PORTO

Portuguese Tile


2x2 Mosaic, 1x3 Herringbone Mosaic, 4x12, 12x12, 12x24, 10x22, 3x10 Bullnose, 4x12 Bullnose

TILE

AMERICA

SHADE VARIATION

V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.



SILVER



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 8 mm

Characteristics:	Norms:	Results
Bond Strength	ASTM C482	≥ 50 psi
Chemical Resistance	ASTM C650	GL: GA, GLA
Water Absorption	ASTM C373	≤ 0.5 %
Abrasion Resistance	ASTM C1027	4
Breaking Strength	ASTM C648	≥ 140 kN
Frost Resistance	ASTM C1026	Resists
Dynamic Coefficient of Friction	AcuTest	0.53

STEEL GREY



LIGHT SAND



Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com