

GLACIER



SAFFIRE

Wood Look

7.75 x 36


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 10.5 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5%
Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 250 lbf
Dynamic Coefficient of Friction Wet	AcuTest	0.45
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household	ISO 10545-13	Class A
Chemical Resistance - Acids	ISO 10545-13	Class A
Resistance to Stains	ISO 10545-14	Class A

Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Stocked in CT!

Book An Appointment



www.tileamerica.com



FUME