

SKY




STONEWAYS TILE

Stone Look
2x2 Mosaic, 12x24, 3x24 Bullnose

AMERICA

SHADE VARIATION

V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.



FLIGHT



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

THICKNESS: 9 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5%
Breaking Strangth	ASTM C648	≥ 250 lbs
Dynamic Coefficient of Friction Wet	AcuTest	0.42
Thickness Dimension	ASTM C499	Conforms
Facial Dimension	ASTM C499	Conforms
Warpage Diagonal	ASTM C485	Conforms
Wedging	ASTM C502	Conforms
Frost Resistance	ASTM C1026	Frost Resistant
Scratch Hardness	MOHS	6

VELVET



NIGHT



Notes:

Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com