

WHITE

STUDIO HEX


Solid Hexagons
8x9

TILE AMERICA

SHADE VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

V2 - Slight Variation



WEAR CODE

White & Silver are rated 4 for all residential and light commercial.
Black is rated 2 for light residential applications.

SILVER

PERFORMANCE DATA

THICKNESS: 10 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.50 %
Abrasion Resistance (Glazed)	ISO 10545-7	4/3/2
Breaking Strength	ISO 10545-4	≥ 30-40 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	0.68
Dimensions	ISO 10545-2	Conforms
Chemical Resistance	ISO 10545-13	Conforms
Thermal Shock Resistance	ISO 10545-9	Conforms
Resistance to Stains	ISO 10545-14	Class 5
Frost Resistance	ISO 10545-12	Frost Resistant
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resists

Notes:

Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An
Appointment



www.tileamerica.com

BLACK