

PURE



# STYLE

Modern Look  
2x2 Mosaic, 12x24, 3x24 Bullnose


# TILE

AMERICA

## SHADE VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

V2 - Slight Variation



LIVELY



## WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

## PERFORMANCE DATA

THICKNESS: 9 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5 %
Breaking Strength	ASTM C648	≥ 400 lbs
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Thickness Dimension	ASTM C499	In Accordance
Facial Dimension	ASTM C499	In Accordance
Warpage Diagonal	ASTM C485	In Accordance
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Unaffected
Scratch Hardness	MOHS	6
Wedging ASTM	C502	In Accordance

ELEGANT



RICH



## Notes:

Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com