


MARFIL



VISION




TERRACOTTA




BLANCO



PERLA



AZUL



OCEAN



SALVIA



TAPESTRY

Fabric Look
4x16, 12x36


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 1 Rated for wall application only

9.3mm Thickness: 4x16

10.6mm Thickness: 12x36

PERFORMANCE DATA

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	> 10%
Abrasion Resistance	ISO 10545-7	1
Breaking Strength	ISO 10545-4	≥ 13 N/mm ² (4x16); ≥ 19 N/mm ² (12x36)
Chemical Resistance		
Household Chemicals	ISO 10545-13	A/LA/HA
Chemical Resistance		
Low Concentration of Acids	ISO 10545-13	A/LA/HA
Resistance to Stains	ISO 10545-14	Class 5 (4x16); Class 3 (12x36)

Notes:

Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Minimum Recommended Grout Joint for PRESSED tiles is no less than 3/16". Minimum Recommended Grout Joint for RECTIFIED tiles is no less than 1/8". Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com