

BYBLOS



# TERRA

Stone Look


2x2 Mosaics, 8x8, 8x16, 16x16, 16x24

# TILE

AMERICA

## SHADE VARIATION

V4 - Random Color differences from tile to tile, so that one tile may have totally different colors from that of other tiles. Thus the final installation will be unique.



DOR



## WEAR CODE

Dor - Class 5 Suitable for all Residential and Commercial Application.  
All other colors - Class 4 All Residential and Light Commercial Applications.

## PERFORMANCE DATA

THICKNESS: 10 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.2 %
Abrasion Resistance	ISO 10545-7	4 / 5
Breaking Strength	ISO 10545-4	≥ 35 N/mm <sup>2</sup>
Dynamic Coefficient of Friction	AcuTest	0.68
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance		
Household Chemicals	ISO 10545-13	GA/GLA/GHA
Chemical Resistance		
Low Concentration of Acids	ISO 10545-13	GA/GLA/GHA
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

## Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com

ERICE



MENFI

