

WHITE



TIBURON

Stone Look

2x2 Mosaic, 4x12, 10x22, 10x22 Wave, 12x12, 12x24, 3x10 Bullnose, 4x12 Bullnose


TILE

AMERICA

SHADE VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

V2 - Slight Variation



BEIGE



WEAR CODE

10x22 / Bullnose: Class 1 Rated for wall application only
Silver: Class 4 All Residential and Light Commercial Applications.
Beige, Light Grey, White: Class 5 Suitable for all Residential and Commercial Application.

PERFORMANCE DATA

THICKNESS: 8 mm

Characteristics:	Norms:	Results
Abrasion Resistance	ASTM C1027	4 / 5
Breaking Strength	ASTM C648	≥ 140 kN
Bond Strength	ASTM C482	≥ 50 psi
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Thickness Dimension	ASTM C499	In accordance
Facial Dimension	ASTM C499	In accordance
Warpage Diagonal	ASTM C485	In accordance
Wedging	ASTM C502	In accordance
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	GL: GA, GLA

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 18" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com

SILVER



LIGHT GREY

