

WHITE



TAUPE



GREY



BLACK



TOPOGRAPHY TILE

Stone Look


12x24, 4x24, 2x2 Mosaic, 1x3 Herringbone,
4x4.5 Hexagon, 4x12

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

White: Class 5 Suitable for all Residential and Commercial Application.
All other colors: Class 4 All Residential and Light Commercial Applications.

PERFORMANCE DATA

THICKNESS: 9 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Resistant
Chemical Resistance	ISO 10545-13	Conforms
Thermal Shock Resistance	ISO 10545-9	Conforms
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 18" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com