

BIANCO



# VERMONT

Stone Look  
2x2 Mosaic, 12x24


# TILE

AMERICA

SHADE VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

V2 - Slight Variation



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

CREAM



## PERFORMANCE DATA

THICKNESS: 8.5 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	~ 0.2 %
Deep Abrasion	ASTM C1243	~ 40 mm <sup>3</sup>
Abrasion Resistance	ASTM C1027	5
Breaking Strength	ASTM C648	≥ 275 lbs
Bond Strength	ASTM C482	≥ 50 psi
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Thickness Dimension	ASTM C499	Complies
Facial Dimension	ASTM C499	Complies
Warpage Diagonal	ASTM C485	Complies
Wedging	ASTM C502	Complies
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Complies
Scratch Hardness	MOHS	6

## Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com



GRAY